

NATA Accredited Laboratory

Laminex

Accreditation No: 15305

a division of Laminex Group Pty Ltd ABN 98 004 093 092

Accredited for compliance with ISO/IEC 17025 - Testing

The Laminex Group Technology Centre

Postal Address: PO BOX 720, Wendouree, Vic 3355 Address: 22 Trewin St, Wendouree, Vic 3355 Telephone: (03) 5337 3613 Fax: (03) 5337 3647

Test Report No. 20MDF-Lamiwood

Date of Issue 17/08/2020

Client:
Laminex Australia
22 Trewin St
Wendouree
VIC 3355

This test report shall not be reproduced, except in full, without written approval from The Laminex Group Technology Centre

The material contained is this report is confidential to the entity identified as 'Client' above.

As the sample(s) have been provided by the client, the results contained in this report apply only to the sample(s) as received.

Laminex Sample Reference No.	26214
Client Sample Reference No.	797255
Product:	16mm Laminex Lamiwood Moisture Resistant E0 MDF
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine
Receive Date:	29/06/2020
Condition:	Good.
Testing Performed Date(s):	3-7/7/2020
Specification Standard	AS/NZS 1859.2:2017
Product Classification	>12 to 22mm MR E0 MDF

Test	Method	Unit	Result		Product limit		
			Mean	Std Dev	Limit Value	Standard	Compliance
					Limit value	Clause	
Formaldehyde Emission	AS/NZS 4266.1: 2017	ma/I	0.37	0.01	Maximum	Clause 6.3	PASS E0
Formaldenyde Emission	Section 17	mg/L	0.57	0.01	0.5 (E0)	Table 1	PASS EU

Formaldehyde Emission Class: E0

Comments

As agreed to by the client, compliance to product limits is based solely on the reported test result(s) and no uncertainty of measurement shall be taken into account.

Approved Signatory:

Laminex Sample Reference No.	25625
Client Sample Reference No.	775853
Product:	18mm Laminex Lamiwood Moisture Resistant E0 MDF
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine
Receive Date:	10/03/2020
Condition:	Good.
Testing Performed Date(s):	17-19/3/2020
Specification Standard	AS/NZS 1859.2:2017
Product Classification	>12 to 22mm MR E0 MDF

Test	Method		Result		Product limit		
		Unit	Mean	Std Dev	Limit Value	Standard	Compliance
					Limit value	Clause	
Formaldehyde Emission	AS/NZS 4266.1: 2017	mg/L	0.42	0.01	Maximum	Clause 6.3	PASS E0
Formaldenyde Emission	Section 17	mg/L	0.42	0.01	0.5 (E0)	Table 1	rass Eu

Formaldehyde Emission Class: E0

Comments

As agreed to by the client, compliance to product limits is based solely on the reported test result(s) and no uncertainty of measurement shall be taken into account.

Approved Signatory:

Laminex Sample Reference No.	22575
Client Sample Reference No.	628208
Product:	25mm Laminex Lamiwood Moisture Resistant E0 MDF
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine
Receive Date:	30/04/2018
Condition:	Good.
Testing Performed Date(s):	11-15/5/2018
Specification Standard	AS/NZS 1859.2:2017
Product Classification	>22 to 33mm MR E0 MDF

Test			Result		Product limit		
	Method	Unit	Mean	Std Dev	Limit Value	Standard	Compliance
					Limit value	Clause	
Formaldehyde Emission	AS/NZS 4266.1: 2017	ma/I	0.36	0.02	Maximum	Clause 6.3	PASS E0
Formaldenyde Emission	Section 17	mg/L	0.30	0.02	0.5 (E0)	Table 1	rass Eu

Formaldehyde Emission Class: E0

Comments
As agreed to by the client, compliance to product limits is based solely on the reported test result(s) and no uncertainty of

measurement shall be taken into account.

Approved Signatory:

Laminex Sample Reference No.	22928
Client Sample Reference No.	GymDec 423
Product:	32mm Laminex Lamiwood Moisture Resistant E0 MDF
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine
Receive Date:	20/07/2018
Condition:	Good.
Testing Performed Date(s):	27-31/7/2018
Specification Standard	AS/NZS 1859.2:2017
Product Classification	>22 to 33mm MR E0 MDF

Test	Method	Unit	Result		Product limit			
			Mean	Std Dev	Limit Value	Standard	Compliance	
					Limit value	Clause		
Formaldehyde Emission	AS/NZS 4266.1: 2017		0.32	0.00	Maximum	Clause 6.3	DACC EO	
Formaldenyde Emission	Section 17	mg/L	0.32 0.00		0.5 (E0)	Table 1	PASS E0	

Formaldehyde Emission Class: E0

Comments
As agreed to by the client, compliance to product limits is based solely on the reported test result(s) and no uncertainty of
measurement shall be taken into account.

Approved Signatory:

Laminex Sample Reference No.	23488
Client Sample Reference No.	676358
Product:	18mm Laminex Decorwood Standard E0 MDF
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine
Receive Date:	19/11/2018
Condition:	Good.
Testing Performed Date(s):	26-28/11/2018
Specification Standard	AS/NZS 1859.2:2017
Product Classification	>12 to 22mm STD E0 MDF

Test	Method		Result		Product limit		
		Unit	Mean	Std Dev	Limit Value	Standard	Compliance
					Limit value	Clause	
Formaldehyde Emission	AS/NZS 4266.1: 2017	mg/L	0.36	0.01	Maximum	Clause 6.3	PASS E0
Formaldenyde Emission	Section 17	mg/L	0.30	0.01	0.5 (E0)	Table 1	rass Eu

Formaldehyde Emission Class: E0

Comments

As agreed to by the client, compliance to product limits is based solely on the reported test result(s) and no uncertainty of measurement shall be taken into account.

Approved Signatory:

Laminex Sample Reference No.	24089			
Client Sample Reference No.	704282			
Product:	25mm Laminex Decorwood Standard E0 MDF			
Surface Treatment	Laminated both sides with decorative Low Pressure Melamine			
Receive Date:	1/04/2019			
Condition:	Good.			
Testing Performed Date(s):	5-9/4/2019			
Specification Standard	AS/NZS 1859.2:2017			
Product Classification	>22 to 33mm STD E0 MDF			

Test	Method	Unit	Result		Product limit		
			Mean	Std Dev	Limit Value	Standard	Compliance
					Limit value	Clause	
Formaldehyde Emission	AS/NZS 4266.1: 2017	mg/L	0.45	0.02	Maximum	Clause 6.3	PASS E0
	Section 17				0.5 (E0)	Table 1	

Formaldehyde Emission Class: E0

Comments		
limits is based solely on	the reported test result(s)	and no uncertainty of

As agreed to by the client, compliance to product measurement shall be taken into account.

Approved Signatory: